

ALUMINUM LINE GUARDS

Catalog Number	Diameter Range (inches)		Conductor Construction A W G - M C M					Wire		Properties		Packaging per box	
	Min	Max	ACSR Type	All Aluminum Type	Aluminum Alloy Type	Compacted ACSR Type	Compacted All-Aluminum Type	Diam (inches)	Qty per set	Color " C "	Length (inches) " L "	Units	Weight (Lbs)
21150	0.437	0.463	2/0,6/1		2/0,7W	3/0,6/1		0.121	13	BLUE	27	50	23
21151	0.437	0.463	2/0,6/1		2/0,7W	3/0,6/1		0.121	13	BLUE	39	50	33
21160	0.464	0.49		3/0,7W,19W				0.121	13	GREEN	27	50	24
21161	0.464	0.49		3/0,7W,19W				0.121	13	GREEN	39	50	35
21170	0.491	0.521	3/0,6/1			4/0,6/1		0.121	14	ORANGE	29	50	26
21171	0.491	0.521	3/0,6/1			4/0,6/1		0.121	14	ORANGE	41	50	37
21180	0.522	0.551		4/0,7W-19W				0.121	14	BLACK	29	50	26
21181	0.522	0.551		4/0,7W-19W				0.121	14	BLACK	41	50	37
21190	0.552	0.585	4/0,6/1					0.121	15	RED	31	50	30
21191	0.552	0.585	4/0,6/1					0.121	15	RED	43	50	42
21200	0.586	0.606		266.8,19W				0.146	14	BLACK	31	50	40
21201	0.586	0.606		266.8,19W				0.146	14	BLACK	43	50	55
21210	0.607	0.63	266.8,18/1					0.146	14	WHITE	33	50	42
21211	0.607	0.63	266.8,18/1					0.146	14	WHITE	45	50	57
21220	0.631	0.655	266.8,26/7					0.146	14	YELLOW	33	50	42
21221	0.631	0.655	266.8,26/7					0.146	14	YELLOW	45	50	57
21230	0.656	0.679		336.4/19W				0.146	15	BROWN	35	50	48
21231	0.656	0.679		336.4/19W				0.146	15	BROWN	47	50	64
21240	0.68	0.703	300,26/7					0.146	15	BLUE	35	50	48
21241	0.68	0.703	300,26/7					0.146	15	BLUE	47	50	64
21250	0.704	0.74	336.4,26/7					0.146	16	GREEN	37	25	54

ALUMINUM LINE GUARDS

Catalog Number	Diameter Range (inches)		Conductor Construction A W G - M C M					Wire		Properties		Packaging per box	
	Min	Max	ACSR Type	All Aluminum Type	Aluminum Alloy Type	Compacted ACSR Type	Compacted All-Aluminum Type	Diam (inches)	Qty per set	Color " C "	Length (inches) " L "	Units	Weight (Lbs)
21251	0.704	0.74	336.4,26/7					0.146	16	GREEN	49	25	72
21260	0.741	0.792	397.5,18/1,26/7,24/7					0.146	17	ORANGE	39	25	60
21261	0.741	0.792	397.5,18/1,26/7,24/7					0.146	17	ORANGE	51	25	78
21270	0.793	0.814	477,18/1	477,19W,37W				0.146	18	PURPLE	39	25	64
21271	0.793	0.814	477,18/1	477,19W,37W				0.146	18	PURPLE	51	25	84
21280	0.841	0.898	477,24/7,26/7,30/7					0.146	19	BLUE	41	25	36
21281	0.841	0.898	477,24/7,26/7,30/7					0.146	19	BLUE	53	25	47
21290	0.899	0.954	556.5,24/7,26/7,30/7	477,19W,37W				0.167	18	GREEN	43	25	46
21291	0.899	0.954	556.5,24/7,26/7,30/7					0.167	18	GREEN	55	25	59
21300	0.955	0.986	605,26/7,636 24/7					0.182	17	WHITE	45	25	54
21301	0.955	0.986	605,26/7,636 24/7					0.182	17	WHITE	57	25	68
21310	0.987	1.016	636,26/7,666.6,24/7					0.182	18	YELLOW	45	25	58
21311	0.987	1.016	636,26/7,666.6,24/7					0.182	18	YELLOW	57	25	73
21320	1.017	1.064	715.5,26/7,24/7					0.182	18	BROWN	47	25	60
21321	1.017	1.064	715.5,26/7,24/7					0.182	18	BROWN	59	25	75
21330	1.065	1.098		874.5,37W,61W				0.204	17	GREEN	49	15	44
21331	1.065	1.098		874.5,37W,61W				0.204	17	GREEN	61	15	55
21340	1.099	1.153	795,26/7,30/19					0.25	15	ORANGE	49	15	58
21341	1.099	1.153	795,26/7,30/19					0.25	15	ORANGE	61	15	72
21350	1.154	1.208	954,45/7,54/7					0.25	15	PURPLE	51	15	62
21351	1.154	1.208	954,45/7,54/7					0.25	15	PURPLE	63	15	77

